

TITLE

A DEVICE FOR CONTROLLING A HYDRAULICALLY DRIVEN MOTOR

TECHNICAL FIELD

5

The present invention relates to an arrangement for controlling a hydraulically driven motor according to the preamble of patent claim 1 below.

BACKGROUND ART

10

In certain applications, hydraulic motors work under load which varies greatly over time, which has hitherto involved problems by virtue of the fact that the inertia in a conventional hydraulic system can mean that the hydraulic liquid flow is not sufficient for supplying the motor. Another critical situation with a risk of cavitation damage is when the motor is actuated into stop position.

15

DISCLOSURE OF INVENTION

20

The object of the present invention is to eliminate the problems indicated in the introduction so that the motor can be controlled so as to perform its tasks with maximum effectiveness.

25

Said object is achieved by means of an arrangement according to the present invention, the characteristics of which emerge from patent claim 1 below.

DESCRIPTION OF FIGURES

30

The invention will be explained in greater detail below by means of an illustrative embodiment with reference to accompanying drawings, in which

fig. 1 shows a hydraulic system which includes an arrangement according to the invention, and

figs 2-4 show an advantageous example of a flow control valve which is adapted for flow control according to the invention.

PREFERRED EMBODIMENT

A hydraulic system in which the arrangement according to the invention can be applied is accordingly shown in the example according to fig. 1. The system includes a hydraulic fluid duct 1 for a main flow from a hydraulic fluid pump (not shown). Also present is a hydraulic fluid volume v, in which a hydraulic fluid pressure is maintained. Hydraulic fluid under pressure is the driving medium adapted to drive a hydraulic motor 2, included in the system, with an output rotation shaft 3, which is adapted to drive some form of unit which is to perform a certain task, for example a saw 11, such as a chain saw, in a harvester unit 12 for lumbering, to be precise sawing lumber. In this connection, the sawing unit and the hydraulic motor with its output rotation shaft are subjected to great instantaneous variations in load, entailing a risk of great instantaneous speed variations. Examples of types of hydraulic motor used for such applications are hydraulic axial piston machines of the bent axis type (see, for example, US 6 336 391) or alternatively the inline type. Other types of hydraulic motor are also possible, for example a gear motor. The hydraulic motor has an inlet side 4, on which the hydraulic fluid is supplied under pressure, and an outlet side 5, from which the hydraulic fluid flows onward in the main duct 1 after pressure drop in the motor. The hydraulic system also includes a flow control valve 7, which is suitably of two-way type, with an inlet 8 and an outlet 9 and a throughflow 10 in a movable valve body, which can be adjusted between open and closed position under the action of an electrohydraulic actuator valve 6, which is adjustable between off position and on position, that is to say stop position

and start/operating position, by means of an actuating device (not shown), which is actuated by an operator/computer.

The flow control valve 7 according to the invention is connected downstream of the hydraulic motor 2 on its outlet side 5 and has, in addition to the start/stop function, a constant flow function which is adapted so as, when the actuator valve 6 is in operating position and hydraulic flow passes through the flow control valve, to maintain an essentially constant hydraulic flow through the hydraulic motor 2, in principle irrespective of load variations of the motor. The throughflow of the flow control valve 7 is adapted to vary its throughflow area depending on the prevailing flow. In the example, this is sensed by sensing pressure drop across a following change in area, for example a narrowing 15, in the main duct 1 via a control duct 16 and via a control duct 22, which is connected to the main line 1 upstream of the narrowing 15, in which way the flow through the motor is controlled by means of the flow control valve depending on the pressure difference across the narrowing. The pressure-sensing upstream of the narrowing is led via the actuator valve 6. However, the narrowing can alternatively be positioned in locations in the system other than downstream of the constant flow valve, as is shown in the figure, for example upstream of the motor 2 or between the motor and the valve. Connected around the motor 2 is a shunt line 24, which includes a non-return valve 25, which is adapted for relieving pressure by being capable of opening in the event of pressure surges on the outlet side of the motor.

25

An example of an embodiment of the flow control valve 7 is shown in figs 2-4. In this example, the valve body in the flow control valve 7 is embodied as a slide 26 in the form of a piston, which is movable linearly to and fro in a cylindrical bore 27 under the action of on the one hand two counteracting control pressures via the control ducts 16, 20, 22, which lead from the two sides of the narrowing 15 to their respective control input 21, 28 and on the other hand the force from the spring 18. The actuator valve 6 is connected in

30

the same way as described with reference to fig. 1, that is to say connected in one control duct 20, 22 between the narrowing 15, upstream thereof, and the control input 28. The control pressures act in their respective cylinder chamber part 30, 31 on the two sides of the piston/the slide 26 and create a pressing force against the respective piston surface 32, 33. The spring 18, which is suitably adjustable with regard to its spring preloading, provides the necessary additional force in order to determine at which pressure drop across the narrowing 15, and thus which speed of the motor, the slide begins to move. Arranged in the valve housing are a number of ducts for the hydraulic flows to be regulated by means of the valve. The main flow, that is to say the flow which drives the motor 2 and is to be regulated by the flow control valve 7, enters via the inlet 8 and flows out via the outlet 9. Flow regulation is effected by virtue of the throughflow 10 of the slide being formed by a passage in the form of an annular groove 34 and a bar 35 with a throttling edge 36 in the lateral wall 37 of the slide 26. By means of the axial displacement of the grooves under the action of the control pressures and the spring 18, the flow area between the inlet 8 and the outlet 9 is regulated, in which way the main flow is regulated. As indicated by dashed lines, the throttling edge 36 can be designed with throttling grooves 38, the design of which influences the control characteristic.

The functioning of the hydraulic system will now be described with reference to all the figures. The general operating requirement for the invention is that as constant an optimized speed as possible of the motor 2 and its output rotation shaft 3 is to be maintained during normal operation and that extreme, instantaneous changes in speed are to be counteracted to as great an extent as possible, in spite of instantaneous load fall-off. An example of such an application is therefore sawing through a log 23, where the risk of what is known as racing arises owing to accumulated energy in hoses etc. symbolized by v , when the log has been sawn through and the load falls off. This is achieved by the flow control valve 7 being dimensioned to work with a rapid response and by this valve being positioned downstream of the motor

2, that is to say on its outlet side 5. When the actuator valve 6 is in stop position, the flow control valve 7 is controlled so as to be closed by the action of system pressure, that is to say full fluid pressure via the control duct 17, and control pressure from the control duct 20 counter to the action of the
5 force from the valve spring 18. In the stop position, the pump pressure acts via the control duct 20 and via one control input 28 of the control valve 7 on one side 32 of the slide, which results in the slide 26 moving into end position and shutting off the entire main flow (see fig. 4). It can be seen from the figure that the bar 35 completely blocks communication between the inlet
10 8 and the outlet 9. Any load-sensing via a sensing duct 19 senses low pressure at the same time. If the pump pressure should fall, the force holding the flow control valve closed decreases. On the other hand, the force for rotating the motor decreases at the same time.

15 When the actuator valve 6 is adjusted from stop position to start position/acceleration position, the flow control valve 7 is opened by the spring 18 and is kept open because the control area is now acted on by the pressure in the control duct 22, which, in the start position, is the same as in the control duct 16 (see fig. 3). It can be seen that the slide 26, by virtue of
20 the action of the spring (compression spring), is displaced to the right in the figure in such a way that the bar 35 with its throttling edge 36 leaves the inlet open.

During operation, the flow control valve 7 works as a constant flow valve, the
25 aim being to keep the hydraulic fluid flow through the flow control valve, and thus through the motor 2, constant by virtue of the valve being fully open when the flow is too low, and seeking to throttle the flow, that is to say brake the motor, when the flow is too high. If load-sensing is present, system pressure is sensed, which provides maximum flow. On stopping, the motor is
30 braked on the rear side by the actuator valve 6 being adjusted to stop position again, the flow control valve 7 then being adjusted to closed position.

In the case of both constant flow control and stopping, the hydraulic fluid pressure at the motor inlet 4 is guaranteed the whole time by the system according to the invention, in contrast to known solutions with a compensator and a stop valve before the motor, where there is a risk of the motor running faster than the flow is sufficient for and thus rotating like a cavitating pump. By virtue of the start/stop function and the constant flow function being integrated in one and the same valve component, a compact construction and short fluid ducts for the main flow, especially between the valve and the motor, are made possible. For example, the valve can be integrated with the motor block, that is to say the motor housing.

The invention is not limited to the examples described above and shown in the drawings but can be varied within the scope of the patent claims below. For example, the load can be a linear motor, such as a piston cylinder. The flow control valve 7 can have a different construction; for example, the valve body can be adapted to be rotated under the action of two counteracting start flows, the throughflow passage then being designed differently.